



Cleaner I

Product

Simson Cleaner I is a preparation agent, ideally suitable for cleaning and degreasing substrates for bonding or sealing with specific Simson products. Consult the Technical Data Sheet of the particular product.

Applications


- Cleaning and degreasing of ceramic coated glass.
- Cleaning and degreasing of plastic.
- Cleaning and degreasing of closed substrates (consult Bostik for more information).
- Removing uncured sealant and adhesive, based on Silyl Modified Polymer (SMP) from substrates and tools.

Method of use

The substrates should be firmly rubbed with a clean, colourless cloth, wetted with Cleaner I. In case the substrate is strongly contaminated repeat this once more.

Note: It is recommended to carry out a trial in advance on a small piece, to check whether the substrate will be affected by Cleaner I.

Drying time: It is recommended to allow a drying time of 5 minutes (at 20°C/50% R.V.). In case of any doubt please consult Bostik.



ADHESIVES AND SEALANTS

Cleaner I

Technical data

Dry contents	0%
Specific gravity	0.79 g/ml
Flash point	12°C
Colour	transparent
Packaging	2.5 litre jerrycan

Storage stability

Cleaner I can be stored for 12 months in an original, unopened container in a dry place at temperatures between +5°C and +30°C.

Further information

The following publication is available on request:

- Material Safety Data Sheets (MSDS)

UK

Bostik Ltd.
Stafford
Tel: +44 (0) 1785 27 27 27
Fax: +44 (0) 1785 22 26 65

France

Bostik S.A.
Paris
Tel: +33 (0) 1 74 96 91 18
Fax: +33 (0) 1 47 96 94 20

Germany

Bostik GmbH
Borgholzhausen
Tel: +49 (0) 54 25/8 01-0
Fax: +49 (0) 54 25/80 11 40

The Netherlands

Bostik B.V.
's-Hertogenbosch
Tel: +31 (0) 73 6 244 244
Fax: +31 (0) 73 6 244 344

For more Bostik locations please consult www.bostik.com

**Bostik**
The Adhesive Company

All figures, recommendations and safety precautions are based on thorough investigations and our actual experience and are without engagement. Although the documentation has been set up with most carefulness, we do not accept any responsibility for mistakes, inaccuracies or printer's errors. We reserve the right to adjust the product, whenever we feel necessary. Because the design, the quality of the substrate and the conditions during application fall beyond our control, no responsibility for executed works can be accepted on the basis of this documentation. We therefore recommend to carry out own tests on the spot. All our sales and deliveries are subject to our general sales- and delivery conditions.