



Mandurax

Product

Simson Mandurax is mineral product with a high toughness and hardness. After diamond, Mandurax is the hardest material that is found in nature.

Application

Mandurax is used as an antiskid material for floor finishing of a Marothaan floor.

Features

- Wear-resistant; Mandurax is broken and sifted in such a way that hard and sharp grains exist, which ensure a maximum wear-resistance.
- Rust-free; Mandurax doesn't even rust in the most unfavourable circumstances and keep its original colour.
- Antiskid; Because of the uneven planes of fracture of the grains, the Marothaan floor scattered with Mandurax has excellent antiskid properties.
- Acidproof; Mandurax has a good resistance against the influences of acids.

Method of use

Application process: Apply at a temperature between +15°C and +25°C at a relative humidity of 40% to 60%.

Substrate: Marothaan.

Application: Approximately 2 hours (at 20°C and 55% R.H.) after applying Marothaan, the floor can be scattered with Mandurax grains. After 3 to 4 hours the floor is cured sufficiently to walk on it and finish it with Simson Marotop 2316.

Consumption: Approx. 0,5 kg/m² (depending on the type of Mandurax and the desired antiskid properties).



Mandurax

Characteristics

Grain size:

Mandurax extra fine	0,7 – 1,2 mm
Mandurax D113	1,0 – 2,0 mm
Mandurax D111	2,0 – 3,0 mm
Mandurax D116	2,5 – 4,0 mm
Packaging	25 kg bag

Storage stability

Store Mandurax in a cool and dry place at temperatures between +15°C and +25°C. Mandurax is kept well for an unrestricted time in its original, unopened packaging.

Further information

The following publication is available on request:

- Material Safety Data Sheets (MSDS Sheet)

UK

Bostik Ltd.
Stafford
Tel: +44 (0) 1785 27 27 27
Fax: +44 (0) 1785 22 26 65

France

Bostik S.A.
Paris
Tel: +33 (0) 1 74 96 91 18
Fac: +33 (0) 1 47 96 94 20

Germany

Bostik GmbH
Borgholzhausen
Tel: +49 (0) 54 25/8 01-0
Fax: +49 (0) 54 25/80 11 40

The Netherlands

Bostik B.V.
's-Hertogenbosch
Tel: +31 (0) 73 6 244 244
Fax: +31 (0) 73 6 244 344

For more Bostik locations please consult www.bostik.com

Bostik
The Adhesive Company

All figures, recommendations and safety precautions are based on thorough investigations and our actual experience and are without engagement. Although the documentation has been set up with most carefulness, we do not accept any responsibility for mistakes, inaccuracies or printer's errors. We reserve the right to adjust the product, whenever we feel necessary. Because the design, the quality of the substrate and the conditions during application fall beyond our control, no responsibility for executed works can be accepted on the basis of this documentation. We therefore recommend to carry out own tests on the spot. All our sales and deliveries are subject to our general sales- and delivery conditions.